

```
[root@dxb-dns-f501:Active:Standalone] config # tms show net packet-tester security dst-addr
18.64.141.78 src-addr 192.168.1.2 protocol icmp src-vlan /Common/INTERNAL_VLAN
Packet SrcIP/Port:192.168.1.2/0 Src Vlan /Common/INTERNAL_VLAN
Packet DstIP/Port:18.64.141.78/0 Dst Vlan unset
Packet Protocol: icmp
Packet Trace Option: Check Staged:Disable, Trigger Log:Disable
```

```
Stage:Device-IP Intelligence
Result: Allow (No Policy)
```

```
Stage:Device-DoS
Result: Allow (No Anomaly)
```

```
Stage:Device-Access Control
Result: Allow (No Policy)
```

```
Stage:Route Domain-IP Intelligence (/Common/0)
Result: Allow (No Policy)
```

```
Stage:Route Domain-Access Control (/Common/0)
Result: Allow (No Policy)
```

```
Stage:Listener-IP Intelligence (/Common/Forwarding_IP_VS)
Result: Allow (No Policy)
```

```
Stage:Listener-DoS (/Common/Forwarding_IP_VS)
Result: Allow (No Policy)
```

```
Stage:Listener-Access Control (/Common/Forwarding_IP_VS)
Result: Allow (Decisive)
```

```
Stage:Device Default
Result: Not Applicable
```

```
Flow Acceptance Decision
Packet SrcIP/Port:192.168.1.2/0 Src Vlan /Common/INTERNAL_VLAN
Packet DstIP/Port:18.64.141.78/0 Dst Vlan unset
Packet Protocol: icmp
Packet Trace Option: Check Staged:Disable, Trigger Log:Disable
Final Action : Allow
```

```
Firewall NAT translation result
Policy Name: /Common/NAT_Policy
Rule Name: unset
Source Translation:
  Translation Object Name: /Common/NAT_5
  Translation Type: Static NAT
  Translated IP Address: 3.3.3.2
  Translated Port: 0
```

Destination Translation:

Translation Object Name: unset
Translation Type: Transparent
Translated IP Address: 18.64.141.78
Translated Port: 8

Total records returned: 1

[root@dx-b-dns-f501:Active:Standalone] config #

```
[root@dx-b-dns-f501:Active:Standalone] config # tms show net packet-tester security dst-addr 8.8.8.8
dst-port 53 src-addr 192.168.1.2 src-port 55559 protocol udp src-vlan /Common/INTERNAL_VLAN
Packet SrcIP/Port:192.168.1.2/55559 Src Vlan /Common/INTERNAL_VLAN
Packet DstIP/Port:8.8.8.8/53 Dst Vlan unset
Packet Protocol: udp
Packet Trace Option: Check Staged:Disable, Trigger Log:Disable
```

Stage:Device-IP Intelligence
Result: Allow (No Policy)

Stage:Device-DoS
Result: Allow (No Anomaly)

Stage:Device-Access Control
Result: Allow (No Policy)

Stage:Route Domain-IP Intelligence (/Common/0)
Result: Allow (No Policy)

Stage:Route Domain-Access Control (/Common/0)
Result: Allow (No Policy)

Stage:Listener-IP Intelligence (/Common/Forwarding_IP_VS)
Result: Allow (No Policy)

Stage:Listener-DoS (/Common/Forwarding_IP_VS)
Result: Allow (No Policy)

Stage:Listener-Access Control (/Common/Forwarding_IP_VS)
Result: Allow (Decisive)

Stage:Device Default
Result: Not Applicable

Flow Acceptance Decision
Packet SrcIP/Port:192.168.1.2/55559 Src Vlan /Common/INTERNAL_VLAN
Packet DstIP/Port:8.8.8.8/53 Dst Vlan unset
Packet Protocol: udp
Packet Trace Option: Check Staged:Disable, Trigger Log:Disable
Final Action : Allow

Firewall NAT translation result
Policy Name: /Common/NAT_Policy
Rule Name: unset

Source Translation:
Translation Object Name: /Common/NAT_5
Translation Type: Static NAT
Translated IP Address: 3.3.3.2
Translated Port: 55559

Destination Translation:
Translation Object Name: unset
Translation Type: Transparent
Translated IP Address: 8.8.8.8
Translated Port: 53

Total records returned: 1

[root@dxb-dns-f501:Active:Standalone] config #

```
[root@dxb-dns-f501:Active:Standalone] config # tms show net packet-tester security dst-addr
18.64.141.78 dst-port 443 src-addr 192.168.1.2 src-port 55559 protocol tcp src-vlan
/Common/INTERNAL_VLAN
Packet SrcIP/Port:192.168.1.2/55559 Src Vlan /Common/INTERNAL_VLAN
Packet DstIP/Port:18.64.141.78/443 Dst Vlan unset
Packet Protocol: tcp
Packet Trace Option: Check Staged:Disable, Trigger Log:Disable
```

Stage:Device-IP Intelligence
Result: Not Applicable

Stage:Device-DoS
Result: Allow (No Anomaly)

Stage:Device-Access Control
Result: Not Applicable

Stage:Route Domain-IP Intelligence (unset)
Result: Default

Stage:Route Domain-Access Control (unset)
Result: Not Applicable

Stage:Listener-IP Intelligence (No Listener)
Result: Not Applicable

Stage:Listener-DoS (No Listener)
Result: Not Applicable

Stage:Listener-Access Control (No Listener)
Result: Not Applicable

Stage:Device Default

Result: Not Applicable

Flow Acceptance Decision

Packet SrcIP/Port:192.168.1.2/55559 Src Vlan /Common/INTERNAL_VLAN

Packet DstIP/Port:18.64.141.78/443 Dst Vlan unset

Packet Protocol: tcp

Packet Trace Option: Check Staged:Disable, Trigger Log:Disable

Final Action : Allow

Firewall NAT translation result

Policy Name: unset

Rule Name: unset

Source Translation:

Translation Object Name: unset

Translation Type: Transparent

Translated IP Address: ::

Translated Port: 0

Destination Translation:

Translation Object Name: unset

Translation Type: Transparent

Translated IP Address: ::

Translated Port: 0

Total records returned: 1

[root@dxb-dns-f501:Active:Standalone] config #